



Planck/LFI Ground Tests: data management and analysis

A. Zacchei¹, M. Maris¹, S. Fogliani¹, M. Salomon², D. Maino³, E. Franceschi⁴,
M. Malaspina⁴, A. Mennella⁵, P. Leutenegger⁶, M. Miccolis⁶, F. Pasian¹,
M. Bersanelli³

¹ INAF/Osservatorio Astronomico di Trieste, Via G.B.Tiepolo 11, I-34131, Trieste, Italy

² Instituto de Física de Cantabria, Facultad de Ciencias, Av. de los Castros, 39005 Santander, Spain

³ università degli studi di Milano, Dipartimento di Fisica, Via Celoria 16, I-20131 Milano, Italy

⁴ IASF/Istituto di Astrofisica Spaziale e Fisica Cosmica, Via P. Gobetti 101, I-40129 Bologna, Italy

⁵ IASF/Istituto di Astrofisica Spaziale e Fisica Cosmica, Via Bassini 15, I-20133 Milano, Italy

⁶ LABEN S.p.A., SS. Padana Superiore 290, I-20090 Vimodrone (Milano), Italy

Abstract. Ground Tests are a fundamental milestone within the development of the Low Frequency Instrument (LFI) which will fly onboard the ESA satellite PLANCK. They allow the collection of information which can not be supplied by monitoring onboard activity of the satellite during operations. Here methods and principles driving the management and elaboration of data collected during the Ground Tests campaign for the PLANCK/LFI are synthetically presented. Ground Tests take place in LABEN (Milano) and will last for about one year.

Key words. PLANCK/LFI – Methods: Data Analysis – Ground Tests

1. Introduction

The ESA satellite PLANCK¹, is the 3rd generation of CMB space missions (after COBE and WMAP) designed to produce measurements of temperature anisotropy over full sky (Burigana et al. 1998). PLANCK will operate as a surveyor

equipped with a 1.5 m Gregorian aplanatic telescope, carrying in the focal surface two instruments covering the frequency bands 30, 44, and 70 GHz (Low Frequency Instrument, LFI, Mandolesi et al. 1998, Pasian 2003) and 100, 143, 217, 353, 545, and 857 GHz (High Frequency Instrument, HFI). Planned to be launched in February 2007 together with Herschel, its main target is to produce CMB maps of sky at different frequencies and to derive from them the cosmological parameters with an unprecedented resolution (FWHM

Send offprint requests to: A. Zacchei

Correspondence to: via G.B.Tiepolo 11, I-34131 - Trieste - Italy, zacchei@ts.astro.it

¹ <http://astro.estec.esa.nl/Planck/>

cryostatic facility allows programmed variations of the parameters defining the environmental conditions. Each test, aimed at assessing a specific feature of the instrument, is characterized by:

- hardware/software configuration;
- set of constant parameters and the laws by which variable parameters are changed;
- test results;
- assessment of proper telecommands execution for specific operations;
- synthetic test report (e.g.: good, bad, failed, etc.).

Functionalities for real time data integration and formatting as quick-look and real-time data analysis are provided by the RACHEL facility, running at the testing site. RACHEL receives data produced by the controllers of the testing facility and from the data acquisition electronics through TCP/IP sockets. The bulk of data is represented by radiometric chains output which are tested in groups of four and are sampled at a frequency of about 8 KHz with a 14 bits acquisition electronics. The other sources of information (sensors, asynchronous events, comments from the operators and soon) are sampled at a much lower rates. RACHEL performs quick-look display and real-time analysis of data through a system of panels and strip-charts displaying acquired data and/or the tests results. RACHEL allows simple statistical analysis (real-time determination of statistical moments, histogramming, FFT, time-series correlations). At last RACHEL integrates the various sources of real time information and store them in a local data store. Information from RACHEL are stored as FITS files, according to a simple predefined standard. Four kinds of FITS files are generated from each test according to the four classes of raw data generated by the test:

- radiometric data;
- radiometric chain set-up;
- cryostat status;
- log files.

No permanent archival facility is planned at the testing site, but the FITS files of each day of test are permanently stored in couples of

twin DVDs (about one couple of DVD each day) a copy of which are delivered by postal service to the LFI/DPC for the final storage (one delivery per week) while the other will be hold at the testing site till the end of the testing campaign. In this way the activities at the testing site are decoupled from the activities at LFI/DPC which will have not to provide a real-time archival service of tests data through internet. At DPC the collection of DVD will represents the bulk of testing data backup, reducing the effort for the preparation of a backup archive. At testing site the DVD collection will represent a data repository whose access is automatically limited to authorized people. The volume of data expected to be gathered during the Ground Test campaign is about 2 Terabyte. LFI Instrument fine-tuning and calibration parameters table will be the result of more refined ground test data streams analysis performed through the RANA tool. This tool consists of an interactive IDL application built on the top of an interface to read RACHEL FITS files, a digital signal analysis methods library tailor-made for LFI Instrument characterization and calibration purposes and finally a report generator. The library is expected to grow during Ground Tests as experience will suggest new and interesting analysis to be integrated in RANA in addition to the basic procedures already provided. In addition the RANA library will represent a prototype for the Quick-Look and Trend Analysis development to be applied to satellite data during the mission at LFI/DPC. At the opposite of RACHEL, which will be installed only at the testing site and maintained only up to the end of the test campaign, RANA will be installed and operated at any site interested to off-line analysis of Ground Test information and likely will be maintained all over the mission.

The Data Archive operated by the LFI/DPC will provide services for Ground Tests data ingestion and retrieval by keyword search (Zacchei et al. 2003b). The archive will be automatically feed through a FITS Ingestor with the data produced by RACHEL and stored in DVD. The FITS Ingestor will extract from FITS files all the needed keywords required to prepare tables for a fast retrieval of

test products. Once consolidated, the results of RANA as the connected documentation are delivered through Internet and ingested in the LFI/DPC archive through a PHP WEB interface. Storage of RANA output follow rules similar to those used for the RACHEL products. The path leading to each result will have to be fully traceable and linked to the specific version of RANA which has been used to obtain it, the same for the site from which the contribution has been originated. It is important to note that the permanent archival of testing data is fundamental in order to exploit the full potential of ground test information along the mission. Archived data will be helpful not only to characterize the instrument but also for calibration and diagnostic during the flight. The archive is placed at the LFI/DPC since it will be the most important consumer of such information during operations. Permanent use of archived data requires to keep information self consistent in time, as to assure full traceability of the physical conditions, of the procedures and of the data analysis algorithm leading to a particular result. For this reason the archive will be ingested both with raw data from the testing facility, metadata including the history of tests and data analysis modules which contributed to the generation of a particular data product. In addition it has to be taken in account that tests will evolve as experience will be gained on the behaviour and analysis of the real instrument. Flexibility

in the data model assumed for the archive and the exchange data format is then an asset.

3. Conclusions

The entire Ground Tests data processing chain is under test at LABEN with good results from the analysis and performance point of view. The design used to develop the Ground Tests data management for PLANCK/LFI can be easily exported to different kinds of instrument.

Acknowledgements. The LFI is funded by the National Space Agencies of the Institutes of the Consortium. In particular the Italian participation is funded by ASI (Agenzia Spaziale Italiana).

References

- Bersanelli M., et al., 2003, PLANCK/LFI Internal Document PL-LFI-PST-PL-008
- Burigana C., et al., 1998, A&AS, 130, 551
- Fogliani S., Malaspina M., Maris M., Zacchei A., Butler R.C., Pasian F., Vuerli C., 2003, Mem S.A.It. Vol 74, 470
- Mandolesi N., et al., 1998, PLANCK/LFI, A *Proposal Submitted to the ESA*.
- Maris M., et al., 2001, PLANCK Int. Rep. PL-LFI-OAT-TN-17
- Pasian F., 2003, Mem S.A.It., Vol 74, 502
- Zacchei A., et al., 2003, PLANCK/LFI Internal Document PL-LFI-OAT-AD-003
- Zacchei A., et al., 2003, PLANCK/LFI Internal Document PL-LFI-OAT-AD-004